





### FASTER

4 Speed dual capstan 9' & 18' on low speed, 20' & 40' on hi speed (per min.) Self contained - ready to pull Quickly change from side pull to overhead, underground or truck hitch No gang box of parts Adjustable counter-balance for easy setup and a 15 lb. working weight Pulls out 10 feet of extra wire Universal adapter

## SAFER

No anchoring required Easy to transport Ergonomic balance point Telescoping User can stand to the side during pulls Easily maneuvers into tight spaces

## SMARTER

Super duty puller will perform on every wire pull No disassembly, fully self-contained Pivoting arm for easy rope access on overhead applications Collapsible Interchangable components for adaptability on the job site Recommened low stretch pulling rope size 5/8" or larger minimum breaking strength 15,000 lbs. Easily extend boom with 2.5" rigid conduit

# INCLUDES

Cannon 10K<sup>™</sup> cable puller (total weight 272 lbs.) Length (fully extended) 10'6" Collapses to 30"w x 45"l x 50"h Universal adapter 5 conduit adapters sizes 2" through 4" (5" & 6" Available) Milwaulkee 4096 power motor, 2 speed, 20 Amp, with 5 year factory warranty Foot switch (UL listed)

## Accessories

PC01- Pull Comms: Hands free noise canceling head sets with case



((

Pull Rope designed for faster wire pulling