



**For all your emergency
and scene lighting**

Hand helds, Searchlights, Head Lamps & LED Flares

Hand Helds



UL-CLASS 1 DIV 1
CLASS 11 DIV 1
CLASS 111

#511907
EX60 Safety Approved
LED Flashlight



#511908
2 in 1 LED Handheld
light converts to head torch



#511902
Zoom LED Flashlight



#511901
Pioneer LED Flashlight



#511903
Commander
High Intensity LED Flashlight



#T0800
Cannon 20 Watt HID Xenon



#T1000
Blaster 25 Watt HID Xenon Torch



#T2500
Survivor 35 Watt HID Xenon Torch



#T2600
Dominator 35 Watt HID Xenon Torch



Searchlights



#511904
Trigger
High Performance
LED Searchlight



#511600
Trio
Long Running
LED Searchlight



#T2600L
Achiever
HID Xenon Torch



Head Lamps



#511905B
HT080
LED Head Torch



#511905A
HT290
High Performance LED Head Torch





LED Flares

Pulsars Emergency Rechargeable LED Hazard Lights

Recharge Time:

12-14 hours (4-6 units)
2-6 hours (1-3 units)



MODE	RUN TIME
1 Rotate	9 hours
2 Quad Flash	9 hours
3 Single Blink	60 hours
4 Alternating Blinks	9 hours
5 SOS Rescue	14 hours
6 Steady ON : High	5 hours
7 Steady ON : Low	35 hours
8 2 LED Flashlight	9 hours
9 4 LED Flashlight	6 hours

Available Colors - Amber, Blue, Yellow, Green

WorkStar

Rechargeable Battery Operated LED Flood Light



#511500



SmithLight

#SL-Traveller Rechargeable Battery Operated LED Light



#IN120LB Rechargeable Battery Operate LED Light



Solaris Lite

Rechargeable LED Lighting System

#5113500S

3.5K Lumen Head & Sealed Lead Acid Battery



#5116000S

6K Lumen Head & Sealed Lead Acid Battery



#5113500L

3.5K Lumen Head & Lithiom Ion Battery



#5116000L

6K Lumen Head & Lithiom Ion Battery



Wobblelight

Portable, Self-Righting Lighting

#111302 (500 watt Halogen)



#111102 (175 watt Metal Halide)



#111104 (400 watt Metal Halide)



Unit	Part Number	Lumen	Run Time	Beam Distance (Meters)	IP Rating	Length	Weight	Battery Type	Bulb Type
EX 60	511907	60	14 hrs	130	IP68	10.2"	6.7 oz	4x AA	LED
2 in 1	511908	85	1 hr	70	IP65	3.7"	2.2 oz	1 x AA	Cree® LED
Zoom	511902	150	5 hrs	200	IP54	4.4"	4.3 oz	3 x AAA	Cree® LED
Pioneer	511901	170	2.5 hrs	200	IP65	3.9"	1.6 oz	1 x AA	Cree® LED
Commander	511903	1000	1.6 hrs	1000	IP65	5.9"	7.1 oz	Lithium Ion	Cree® LED
Cannon	T0800	800	1 hr	450	IPx3	9.5"	1.5 lbs	Lithium Ion	HID Xenon
Blaster	T1000	1000	2 hrs	500	IPx3	12"	2.5 lbs	Lithium Ion	HID Xenon
Survivor	T2500	2500	1h 40m	950	IPx3	14.5"	2.8 lbs	Lithium Ion	HID Xenon
Dominator	T2600	2600	1h 40m	950	IPx3	18"	3.4 lbs	Lithium Ion	HID Xenon
Trigger	511904	210	3 hrs	400	IP65	6.7"	24.7 oz	4.8V 2200mAh Ni-mh	Cree LED
Trio	511600	230	7 hrs	400	IP44	7.4"	35.3 oz	6v 4Ah Sealed Lead Acid	LED
Achiever	T2600L	2600	50m	1000	IPx3	9"	5.7 lbs	Lead Acid Battery	35 watt HID Xenon
HT080	511905B	80	2 hrs	70	IP44	NA	2.6 oz	1 x AA	LED
HT290	511905A	290	3.5 hrs	260	IP65	NA	12.4 oz	4.8V 2200mAh Ni-mh	Cree LED
Pulsars	511401-511409		5-60 hrs		IP68 (up to 10m)	7.1 "	6.7 oz	Lithium Ion	LED

	NightSearcher Work Star	SmithLight Traveller	SmithLight Extended Run	Solaris Lite 3.5K	Solaris Lite 6K	Solaris Lite 3.5K - Lithium Ion	Solaris Lite 6K - Lithium Ion
Part Number	511500	SL-Traveller	IN120LB	5113500S	5116000S	5113500L	5133500L
Lumen	2,200 High/ 1,000 Low	720	1,030 per side	3,500 High/2,000 Low	6,000 High/3,000 Low	3,500 High/2,000 Low	6,000 High/2,000 Low
Run Time	3 hrs/7 hrs	12 hrs	15 hrs 2 sides/30 hrs 1 side	6 hrs/13 hrs	2.5 hrs/5 hrs	7 hrs/14 hrs	3.5 hrs/7 hrs
Lighting Range (ft)	65	20	40	165	260	165	260
Beam Spread/Head (degrees)	30	120	120	30	30	30	30
Mast Head (Max Ft)	NA	2	3.7	4.25	4.25	4.25	4.25
IP Rating	65	65	65	65	65	65	65
Weight	3.4 lbs	12 lbs	24 lbs	23 lbs	23 lbs	14 lbs	14 lbs
Dimensions-Closed (in.)	17 x 9.5 x 4	18 x 10 x 8	24 x 13 x 8	12 x 7 x 5.5	12 x 7 x 5.5	12 x 7 x 5.5	12 x 7 x 5.5
Rated Temp.-Range (F)	-4 to 140	-15 to 115	-15 to 115	-20 to 140	-20 to 140	-20 to 140	-20 to 140
Battery Capacity (Volts/Amp-hours)	7.4V 4.5AH Li-ion	12VDC/7AH	12VDC/18Ah	12 V 17Ah SLA	12 V 17Ah SLA	14.8V 18.2Ah Li-ion	14.8V 18.2Ah Li-ion
Recharge Time (Max Hrs)	4 hrs	8 hrs	12 hrs	8 hrs	8 hrs	7 hrs	7 hrs
Bulb Type	LED	LED	LED	Cree® LED	Cree® LED	Cree® LED	Cree® LED
Approvals	cUL	CSA, UL, CE, RoHS	CSA, UL, CE, RoHS	cUL	cUL	cUL	cUL

	Wobblelight 500watt Halogen	Wobblelight 175watt Metal Halide	Wobblelight 400watt Metal Halide
Part Number	111302	111102	111104
Lumen	8,000	15,000	42,000
Run Time	NA	NA	NA
Lighting Range (ft)	25	45	110
Beam Spread/Head (degrees)	360	360	360
Mast Head (Max Ft)	3	3	3
IP Rating	NA	NA	NA
Weight	27 lbs	29 lbs	31 lbs
Dimensions-Closed (in.)	36 x 18	36 x 18	36 x 18
Rated Temp.-Range (F)	-40 to 110	-40 to 110	-40 to 110
Battery Capacity (Volts/Amp-hours)	NA	NA	NA
Recharge Time (Max Hrs)	NA	NA	NA
Bulb Type	Halogen	Metal Halide	Metal Halide
Approvals	cUL	cUL	cUL



877-707-0800 | www.probuiltlighting.com